Data Types and Storage Engines: How does SQLyog handle TIMESTAMPS defined as '... on UPDATE CURRENT_TIMESTAMP'?

You can read about SQLyog 'smart' KEYWORD handling introduced with SQLyog 5.1 here.

When updating any TIMESTAMP defined with

'... on UPDATE CURRENT TIMESTAMP'

SQLyog will not include that column in the update statement, and the server will replace the old TIMESTAMP with a new **CURRENT_TIMESTAMP**. This is the basic idea with the '... on update ..' clause and is fully supported by SQLyog.

To create a **TIMESTAMP** default **CURRENT_TIMESTAMP** not **NULL** on **UPDATE CURRENT_TIMESTAMP** with MySQL >= 4.1 (and if this TIMESTAMP is the first TIMESTAMP of the table) you will only need to check the 'Not Null' checkbox from SQLyog GUI's (CREATE TABLE, ALTER TABLE). The first TIMESTAMP in a table defined NOT NULL will be created as **TIMESTAMP** default **CURRENT_TIMESTAMP** not **NULL** on **UPDATE CURRENT_TIMESTAMP** by the MySQL server then. SQLyog does not 'override' this in any way.

Unique solution ID: #1083 Author: Peter Laursen

Last update: 2006-03-08 16:58